

Conveniently transport prefiltered coolant to a central recycling system; return processed coolant back to machine tools

- Same CECOR power, deep vacuum and capabilities as the single-tank SE10 Sump Shark®.
- Two completely separate tanks on the same chassis.
- One tank is a sump cleaner for fast removal and filtering of coolant and solids from machine tool sumps*.
- One tank is a dispenser to save time and dispense new coolant immediately back to machine tools.
- Each tank has pump in/pump out capability.
- Reduce machine tool downtime, labor costs and mess. Save time and money.
- Proudly designed and manufactured in the U.S.A.



Tank Size: 60/60-, 100/100-, 150/150-, 200/200-, 250/250- and 300/300-gallon capacity

Motor: 1 HP Electric Motor • Volts 115
Amps 13.4 • Hertz 60 • Phase 1

Pump: Rotary, vane-type vacuum pump

Pumping Rate: Up to 60 gallons (227 liters) per minute

Suction Lift: 17" Hg (Mercury) or 231" (6 meters) water

Pressure Discharge: 6 PSI (pounds per square inch) with safety backup valve

Filter: F10 Filter (1 cu. ft. capacity) is standard. Optional F23 (2.3 cu. ft. capacity) is recommended when coolant is loaded with chips and swarf. Coarse, regular and fine weaves available.

Overfill Prevention: Automatic overfill protection, all discharge ports are valved

Hoses: 1 1/2" I.D. x 16' oil-resistant PVC suction/discharge hose including quick-disconnect coupler and suction tools. Clean coolant dispensing hose of heavy-section clear plastic 1-1/4" I.D. x 16' with full-flow shut-off nozzle.

Accessories: Flared Nozzle • Flexible Nozzle • Straight Nozzle • 50' power cord (15' standard)



**Sump Sharks have proven effective in many types of applications: general machining, screw machines, grinding, water jet cutting, plasma cutting and more. Industrial fluids is a general term we use to mean coolant, metalworking fluids, cutting fluids, etc.*