

### Air-powered Sump Sharks® offer the deepest vacuum, pumping out pits up to 20' deep

- Ditch the grueling pail-n-shovel process! Clean dirty machine tool sumps\* faster, better and safer.
- Effectively filter chips and sludge from industrial fluids for re-use (when applicable). Pick up the thickest of sludge.
- Pump in/pump out capability.
- Convenient use of in-plant air supply.
- No moving parts. Simple to operate and maintain.
- Includes push handle, tow bar and fork pockets.
- Reduce machine tool downtime, labor costs and mess. Save time and money.
- Proudly designed and manufactured in the U.S.A.



<b>Tank Sizes:</b>	60, 90, 140, 200, 300, 400, 500 & 600 gallon
<b>Pump:</b>	Air-operated venturi
<b>Pumping Rates:</b>	Up to 70 gallons (264 L) per minute w/1-1/2" hose Up to 110 gallons (416 L) per minute - 2" hose
<b>Suction Lift:</b>	26" Hg (Mercury) or 350" (9 meters) water
<b>Filter:</b>	F10 Filter (1 cu. ft. capacity) is standard. Optional F23 (2.3 cu. ft. capacity) is available. Multiple media options for finer filtering.
<b>Air Requirements:</b> (optimal performance)	Air headers - 3/4" or larger; Vertical drops - 1/2" or more; Line pressure - 75 to 120 PSI; Volumetric capacity - 53 to 80 CFM.
<b>Overfill Prevention:</b>	Automatic overfill protection, all discharge ports are valved
<b>Pressure Discharge:</b>	6 PSI with safety backup valve
<b>Standard Hose:</b>	1-1/2" I.D. x 16' oil-resistant PVC suction and discharge hose including quick-disconnect coupler and suction tools. Optional 2" hose available.
<b>Transport:</b>	Push/Tow/Lift capable (90 - 200 gal).

### SA5-60PL SUMP SHARK

CECOR's smallest air powered high-end sump cleaner, the SA5-60PL, has a unique vertical design for shops with limited floorspace. High-suction lift sucks out everything in the sump -- chips, fines, particles and fluid.

- 60-gallon tank
- Space-saving vertical design for shops with limited space
- Same power as larger air unit, but in smaller package
- Pumping rate up to 70 gallons (264 l.) per minute
- PL - Push/Lift Base

1 cu. ft. filter standard, optional 2.3 cu. ft. available



\*Sump Sharks have proven effective in many types of applications: general machining, screw machines, grinding, water jet cutting, plasma cutting and more. Industrial fluids is a general term we use to encompass coolant, metalworking fluids, cutting fluids, etc.

**F10 - 1.0 CUBIC FOOT FILTER**

The F10 strainer basket and fabric liner has a capacity of 1.0 cubic foot and is standard on the SA5. The reusable filter has built in grips and is small enough for one person to lift. Coarse, fine and polypropylene filter bags come standard with the F10 filter basket.



Standard F10 Filter

**F23 - 2.3 CUBIC FOOT FILTER (OPTIONAL)**

With a 2.3 cubic feet capacity, the F23 filter is fitted for fork lift or hook hoist handling. Patented compound linkage and rotary latch control the bottom opening door for safe emptying. The filter assembly comes complete with a regular-weave polypropylene filter sleeve. The F23 filter is optional on the SA5. Optional coarse and fine weaves available.



Optional F23 Filter

Available as a combination-tank sump cleaner and coolant dispenser – **CA5 Sump Shark**.

Model	Tank Size	Cleanout Door	Transport Base *	Wheels	Est. Dimensions (L x W x H)	Est. Ship Weight	Filter
SA5-60PL-D	60 gal. (227 L)	2-1/2" drain port in bottom	Standard: PL Base (Push/Lift)	Phenolic wheels: two 8" x 2", one 6" x 2" swivel caster	37" x 33" x 55" 940 x 839 x 1397 mm	370 lbs 168 kg	F10 Std.
SA5-90PTL-H	90 gal. (341 L)	8" x 10" door with a 1-1/4" drain port	Standard: PTL (Push/Tow/Lift) Available: PL6 & CB	Poly tires: two 12" x 3", one 8" x 3" swivel caster	69" x 30" x 54" 1753 x 762 x 1372 mm	630 lbs 286 kg	
SA5-140PTL-H	140 gal. (530 L)				69" x 34" x 59" 1753 x 864 x 1499 mm	745 lbs 338 kg	
SA5-200PTL-H	200 gal. (757 L)				92" x 34" x 59" 2337 x 864 x 1499 mm	880 lbs 400 kg	
SA5-300TW-H	300 gal. (1,136 L)	16" diameter hinged door with a 2-1/2" drain port	Standard: TW Base (Tow-Only)	Rubber tires: two 16" x 4", one 12" x 3" swivel caster	96" x 42" x 65" 2439 x 1067 x 1651 mm	1,110 lbs 504 kg	F23 Opt.
SA5-400TW-H	400 gal. (1,514 L)		Tow bar with pintle-eye hitch to accommodate most in-plant tugs or tractors	Rubber tires: two 16" x 4", two 12" x 3" swivel casters	99" x 46" x 71" 2515 x 1169 x 1804 mm	1,380 lbs 626 kg	
SA5-500TW-H	500 gal. (1,893 L)		Available: CB	Rubber tires: two 16" x 5", two 12" x 3" swivel casters	111" x 48" x 73" 2820 x 1220 x 1855 mm	1,475 lbs 670 kg	
SA5-600CB-H	600 gal. (2,271 L)		Standard: CB (Custom Base) for mounting on trailer or truck	N/A	121" x 42" x 64" 3074 x 1067 x 1626 mm	1,690 lbs 767 kg	

Ask about a floor squeegee and other available accessories (sold separately).

Note: Engineering specifications subject to change without notice.

\*See "Transport Base Options" spec sheet for more information.

- PTL – push/tow/lift base
- PL6 – push/lift base w/ 6 wheels (center-mounted casters) & fork pockets
- TW – tow-only base
- CB – custom bases available

**Caution: Machines must not be used for flammable fluids (fuels, paints, solvents, etc). Avoid use in extra-high temperature or spark-hazard environments (ovens, welding areas, etc).**