

CECOR's single-phase Sump Shark® works conveniently wherever there are standard power outlets

- Ditch the grueling pail-n-shovel process! Clean dirty machine tool sumps* faster, better and safer.
- Effectively filter chips and sludge from industrial fluids for re-use (when applicable). Save on fluid costs and disposal.
- Handy "tool caddy" stores tools and keeps them handy for when you need them.
- "Plug-n-play" convenience. Runs on standard, economical 115/60/1 15 amp electricals. No emissions.
- Generates higher nozzle velocity to pick up both puddles on the floor and dry solids. Pump in/pump out capability.
- Reduce machine tool downtime, labor costs and mess. Save time and money.
- Proudly designed and manufactured in the U.S.A.



Tank Size: 60-, 90-, 140- and 175-gallon capacity

Motor: Vacuum Motor • Volts 115
Amps 14.2 • Hertz 60 • Phase 1

Pumping Rate: Up to 60 gallons (227 liters) per minute

Suction Lift: 13" Hg (Mercury) or 177" (4.5 meters) water

Filter: F10 Filter (1 cu. ft. capacity) is standard. Optional F23 (2.3 cu. ft. capacity) is recommended when coolant is loaded with chips and swarf. Coarse, regular and fine weaves available.

Overfill Prevention: Automatic overfill protection, all discharge ports are valved

Pressure Discharge: 6 PSI (pounds per square inch) with safety backup valve

Hoses: 1 1/2" I.D. x 16' oil-resistant PVC suction/discharge hose including quick-disconnect coupler and suction tools

Accessories: Flared Nozzle • Flexible Nozzle • Straight Nozzle • 50' power cord (15' standard)



** Sump Sharks have proven effective in many types of applications: general machining, screw machines, grinding, water jet cutting, plasma cutting and more. Industrial fluids is a general term we use to mean coolant, metalworking fluids, cutting fluids, etc.*

Caution: Machines must not be used for flammable fluids (fuels, paints, solvents, etc). Avoid use in extra-high temperature or spark-hazard environments (ovens, welding areas, etc).